

Digital Video Recorder NV-DVR1004NET



Features

- SIMPLEX
- Operating system based on Linux
- Real-time display
- Recording speed: up to 25 fps
- M-JPEG compression
- Recording resolution:
 - 640 (H) x 272 (V)
- Supports up to 2 HDDs (max. 500 GB each)
- PTZ control directly from the device and through the network
- Possibility of controlling NOVUS® cameras equipped with RS-485 interface
- Protocols: Novus-C, Novus-C1, Novus-C2, Pelco-D
- Networking through IE browser
- Backup function through the network
- Software: PC Viewer for reviewing and copying parts of recorded data from HDD, DVR_Calc for recording time estimation at given parameters
- User friendly OSD
- Power supply: 100~240 VAC

| Specifications | Description |
|----------------------|--|
| Operation Mode | SIMPLEX |
| Operating System | Linux |
| Video Input | 4 x BNC loop-through, 1.0 Vp-p/75 Ohm |
| Video Output | 1 Main Monitor output (BNC) |
| Alarm Input | 4 |
| Alarm Output | 1 relay output |
| Recording Speed | Up to 25 fps |
| Compression | M-JPEG |
| Recording Resolution | 640 (H) x 272 (V) |
| Recording Mode | Time-lapse, Event (Alarm and/or Motion detection) |
| Display Speed | 100 fps (real-time) |
| Display Screen | 1, 4 |
| Motion Detection | 2 grids with active areas size & sensitivity |
| Video Loss Detection | Yes |
| Schedule Recording | Mode (Time-lapse/Event/Off) & recording speed selection in different times of the day (timed to 1 h) |
| Recorded Data Search | By date/time or events |
| Event History Log | Up to 64 alarm events for each HDD |
| Storage | Supports up to 2 HDDs (max. 500 GB each), 1 to be installed in the swappable drive |

| Specifications | Description |
|-----------------------|--|
| Backup | PC - directly from HDD using the PC Viewer software, network backup |
| External Ports | 1 x Ethernet - RJ-45 1 x RS-485 for PTZ cameras |
| PTZ Functions | PTZ cameras control directly from the device using front panel buttons |
| Protocol | Novus-C, Novus-C1, Novus-C2, Pelco-D |
| Control | Front panel, Network |
| Set-up | Multi-lingual On Screen Display (OSD) |
| Software | DVR_Calc, PC-Viewer |
| User Authorization | Password protection |
| Auto System Recovery | Hardware WATCHDOG function |
| Power Supply | 230 VAC |
| Operating Temperature | 0°C ~ 40°C |
| Relative Humidity | 0 % ~ 80 % (non-condensing) |
| Dimensions (mm) | 432 (W) x 55 (H) x 321 (D) |
| Weight | 4 kg |
| * | Lista zalecanych modeli i pojemności dysków dostępna w załączniku „Kompatybilne dyski” |