

Digital Video Recorder NV-DVR1004 LITE



Features

- SIMPLEX
- Operating system based on Linux
- Real-time display
- Recording speed: up to 25 fps
- M-JPEG compression
- Recording resolution:
 - 640 (H) x 272 (V)
- Software: PC Viewer for reviewing and copying parts of recorded data from HDD, DVR_Calc for recording time estimation at given parameters
- User friendly OSD
- Power supply: 12 VDC

| Specifications | Description |
|----------------------|--|
| Operation Mode | SIMPLEX |
| Operating System | Linux |
| Video Input | 4 x BNC, 1.0 Vp-p/75 Ohm |
| Video Output | 1 Main Monitor output (BNC) |
| Recording Speed | Up to 25 fps |
| Compression | M-JPEG |
| Recording Resolution | 640 (H) x 272 (V) |
| Recording Mode | Time-lapse, Motion detection |
| Display Speed | 100 fps (real-time) |
| Display Screen | Full screen, 4 |
| Motion Detection | 1 grid with sensitivity adjustment (5 levels) |
| Video Loss Detection | Yes |
| Schedule Recording | Mode (Time-lapse/Motion detection /Off) & recording speed selection in different times of the day (timed to 1 h) |
| Recorded Data Search | By date/time or events |
| Event History Log | Up to 64 alarm events for each HDD |
| Storage | Supports 1 HDD (max. 500 GB) |
| Backup | USB PC-LINK using the PC Viewer software |
| Control | Front panel |
| Set-up | Multi-lingual On Screen Display (OSD) |
| Software | DVR_Calc, PC-Viewer |

| Specifications | Description |
|-----------------------|--|
| User Authorization | Password protection |
| Auto System Recovery | Hardware WATCHDOG function |
| Power Supply | 12 VDC (100~240 VAC/12 VDC PSU in-set included) |
| Power Consumption | Approx. 5 W without HDD, approx. 30 W with HDD |
| Operating Temperature | 0°C ~ 40°C |
| Relative Humidity | 0% ~ 80% (non-condensing) |
| Dimensions (mm) | 218 (W) x 44 (H) x 206 (D) |
| Weight | 1,3 kg |
| * | Lista zalecanych modeli i pojemności dysków dostępna w załączniku „Kompatybilne dyski” |