

Monitor LCD NVM-423LCD



Features

- Professional high resolution TFT LCD monitor
 - Digital 3D comb filter for sharp and clear picture with natural colors
 - Panel type: 23"
 - 16:9 LCD panel format
 - 4-channel real-time multiplexer built-in
 - Multi-screen display (PC/Quad/POP screen/Full screen)
 - Image storage: up to 60 still images
 - Digital zoom: 2x
 - Alarm input/output: 1
 - Video input: 4 x BNC, S-Video, VGA, RCA
 - Audio input: RCA
 - Internal speakers
 - Key Lock function and menu password protection
 - Multi-lingual On Screen Display (OSD)
 - Rugged metal design
 - Power supply: 24 VDC (100 ~ 240 VAC/24 VDC PSU in-set included)

Specifications	Description
Panel Type	23" color TFT LCD Panel
Screen Size (Diagonal)	584.2 (mm)
Viewable Size (mm)	501.12 x 300.67 (mm)
CRT Dot Pitch	0.391 x 0.391 (mm)
Resolution	580 TVL
Viewing Angle (L/R/T/B)	85°/85°/85°/85°
Contrast Ratio	400:1
Brightness	450 cd/m ²
Display Color	16.7 mln
Response Time	25 ms
Video Input	4 x CVBS: BNC loop-through connector, 1 x S-Video: Mini-DIN 4 Pin connector, 1 x VGA, 1 x YPbPr: 3 x RCA
Audio Input	Stereo 1 Vp-p/1 kHz
Speaker Output	2 x 2.5 W
Alarm Input	1 input (NO/NC) with individual polarity selection
Alarm Output	1 output (NO/NC)
Operation	Multi-lingual On Screen Display (OSD)
Operation System	PAL/NTSC (Auto Scan)
Case	Metal
Access Security	Key Lock function, menu password protection

Specifications	Description
Power Supply	24 VDC (100 ~ 240 VAC/24 VDC PSU in-set included)
Power Consumption	101 W
Operating Temperature	0°C ~ 40°C
Dimensions (mm)	572 (W) x 385 (H) x 68.9 (D)
Weight	9.5 kg
In-set Included	DC adapter, Power cord, VGA cable, IR remote control