

Day/Night Classic Camera NVC-BDN5402C-2



*lens not included



Features

- Mechanical IR cut filter
- IR operation capability
- Horizontal resolution: up to 650 TVL
- Min. illumination: from 0.01 lx/F=1.2
- Digital Noise Reduction (DNR)
- Privacy zones: 4
- Additional functions: mirror picture effect, motion detection
- Full configuration (user friendly OSD):
 - directly from the camera
 - from the NV-KBD70 & NV-KBD40 keyboards
 - from NOVUS® video capture cards
 - directly from the front panel of selected NOVUS® DVRs
- Remote control: RS-485
- Protocol: Pelco-D
- Power supply: 12 VDC/24 VAC

Specifications	Description
Pick-up Element	1/3" SONY Super HAD II CCD imager
Horizontal Resolution	600 TVL - color mode, 650 TVL - B/W mode
Min. Illumination	0.1 lx/F=1.2 - color mode (1/50 s), 0.01 lx/F=1.2 - B/W mode (1/50 s)
S/N Ratio	More than 50 dB (AGC Off)
Electronic Shutter	Auto (AES): 1/50 s ~ 1/120 000 s
Auto Gain Control (AGC)	On/Off
White Balance	3 modes: Manual/ATW/AWB
Back Light Compensation (BLC)	On/Off
Synchronization	Internal
Day/Night Switching	Automatic/Manual/External
Filter Delay	1 ~ 15 s
Iris Mode	D
Lens Mount	C/CS
Flickerless function	On/Off
Video Output	1.0 Vp-p/75 Ohm (BNC)
Remote Control	RS-485
Protocol	Pelco-D
Set-up	On Screen Display (OSD)
Privacy Zones	4
Other Functions	Digital Noise Reduction (DNR), Motion detection, Mirror picture effect, Image sharpness adjustment

Specifications	Description
Power Supply	12 VDC/24 VAC
Power Consumption	3.6 W
Operating Temperature	-10°C ~ 45°C
Relative Humidity	30% ~ 80% (non-condensing)
Dimensions (mm)	125 (L) x 64 (W) x 58 (H)
Weight	346 g