

## Camere cilindrice Color Iluminare IR NVC-SC320H/IR



### Caracteristici

- Rezolutie orizontala: 420 TVL
- Sensibilitate: 0 lx (IR On)
- Obiectiv standard: f=6.0 mm
- Iluminare IR incorporata - 48 unitati
- IP 65
- Consola de montare si parasolar incluse
- Alimentare: 12 VDC

| Specificatii               | Description  |
|----------------------------|--|
| Pick-up Element            | 1/3" SONY Super HAD HQ1 DSP CCD imager               |
| Number of effective pixels | 752 (H) x 582 (V)                                    |
| Horizontal Resolution      | 420 TVL  |
| Min. Illumination          | 0 lx (IR On)   |
| S/N Ratio                  | > 48 dB (AGC Off)                                    |
| Electronic Shutter         | Auto: 1/50 s ~ 1/100 000 s                           |
| Auto Gain Control (AGC)    | On   |
| White Balance              | Auto   |
| Synchronization            | Internal   |
| Lens Type                  | Standard, f=6 mm                                     |
| Angle of View (H)          | 43.6°  |
| IR LED                     | LED - 48 pcs   |
| IR Effective Range         | Up to 30 m   |
| Video Output               | 1.0 Vp-p/75 Ohm (BNC)                                |
| Degree of Protection       | IP 65  |
| Power Supply               | 12 VDC   |
| Power Consumption          | 1.5 W (IR illuminator Off) 5.5 W (IR illuminator On) |
| Operating Temperature      | -10°C ~ 50°C   |
| Dimensions (mm)            | 70 (Ø) x 102 (L)                                     |
| Weight                     | 650 g  |