

Digital Video Recorder NDR-EA3216



Caracteristici

- QUADRUPLEX: simultaneous recording, live monitoring/playback, backup and networking
- Operating system based on Linux
- Real-time display
- Recording speed: up to 200 fps
- H.264 compression
- Recording resolution:
 - 720 x 576
 - 720 x 288
 - 360 x 288
- Supports up to 3 SATA HDDs (4th HDD instalation possible with additionally purchased mounting kit)
- Recording speed and quality defined individually for each camera
- Advanced schedule recording & motion detection functions
- Pre- & post-alarm functions
- Recording time estimation function
- 4-channel real-time audio recording
- External devices support ("Text-in" feature): ATM, POS, AC etc.
- Advanced search functions of recorded images
- PTZ control directly from the device or through the network
- Protocols: N-Control, Pelco-D, Pelco-P and others
- NV-KBD70 & NV-KBD30 keyboards compatible
- Possibility of installing DVD-RW drive (option)
- Backup: onto HDD or USB Flash Memory through USB port, CD/DVD (option) & through the network
- Networking (simultaneous connections with multiple DVRs and alarm e-mail notification)
- Software: E-Viewer application for remote administration, live monitoring and recorded data search with a built-in callback module (E-Viewer Callback), iMon application for live monitoring, receiving information on alarm events, alarm output control, DVR configuration from iPhone and Android OS devices
- Self-diagnostic functions with automatic notification
- User friendly multi-lingual OSD
- Covert camera function
- IR remote control and PC mouse control (in-set included)
- Power supply: 12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)

Specificatii	Description
Mod de operare	QUADRUPLEX
Sistem de operare	Linux
Intrare Video	16 x BNC, loop-through
Iesire video	Main Monitor (1 x BNC, 1 x VGA), Spot Monitor (1 x BNC)
Intrare Alarm	16
Iesire Alarm	2 OC, 2 relay outputs
Intrare Audio	4 x RCA (Line-in)

Specificatii	Description
Audio Iesire	1 x RCA
Viteza Inregistrare	Up to 200 fps (360 x 288), up to 100 fps (720 x 288), up to 50 fps (720 x 576)
Compresie	H.264
Rezolutie Inregistrare	720 x 576, 720 x 288, 360 x 288
Mod de inregistrare	Time-lapse, Event (Alarm, Motion detection and/or "Text-in")
Viteza de afisare	400 fps (real-time)
Afisajul	Full screen, 4, 9, 1+12, 16, PiP, sequence, user defined, digital zoom of a chosen screen area: 2x, freeze image function
Detectarea de miscare	256 detection windows (16x16 grid) with sensitivity defined individually for each channel
Detectare pierdere semnal video	Yes
Programarea inregistrarii	Individually adjustable for each day/specific days (holidays etc.) per camera, combination of individual recording modes possibility
Cautarea inregistrarilor	By date/time, events, "Text-in"
Jurnal de evenimente	Up to 10 000 alarm events
Sincronizare timp	Automatic time synchronization with NTP server
Diagnostic System	Automatic control of HDD bad sectors number ("Health") & temperature status with local and network notification function
Depozitare	Supports up to 3 SATA HDDs* (4th HDD instalation possible with additionally purchased mounting kit)
Backup	Onto CD/DVD (option), HDD or USB Flash Memory through USB port, through the network
Port-uri externe	1 x Ethernet - RJ-45 interface, 10/100 Mbits/s, 3 x USB 2.0 for external drives (HDD, Flash Memory), 1 x USB 1.1 for PC mouse, 1 x RS-485 & 1 x RS-232 for PTZ cameras, NV-KBD70 & NV-KBD30 keyboards, POS, ATM, AC etc.
Functii PTZ	Directly from the device or through the network
Protocol	N-Control, Pelco-D, Pelco-P and others
Control	Front panel, IR remote controller (in-set included), Network (E-Viewer, iMon, IE), NV-KBD70 & NV-KBD30 keyboards, USB PC mouse (in-set included)
Programare	Multi-lingual On Screen Display (OSD)
Software	E-Viewer, iMon
Autentificare utilizator	Creation of user groups and accounts with diverse grants, password protection
Auto System Recovery	Hardware WATCHDOG function
Alimentare	12 VDC (100 ~ 240 VAC/12 VDC PSU in-set included)
Consum	Approx. 80 W with 4 HDDs
Temperatura de lucru	5°C ~ 40°C
Umiditate	0% ~ 80% (non-condensing)
Dimensiuni (mm)	430 (W) x 88 (H) x 428 (D)
Greutate	6 kg (without HDD)
Rack Mount	Standard EIA 19", 2U
*	The list of recommended disk models and their capacity is available on Novus Security website in the Compatible Disks file in the product tab