

Color Dome Camera NVC-BC2403D/IR-white-II



Caracteristici

- IR operation capability
- Horizontal resolution: 600 TVL
- Min. Illumination: (0 lx - IR On)
- Standard lens: f=3.6 mm
- 3-axis camera module adjustment
- Built-in visible light sensor
- Built-in IR LED - 24 pcs.
- IR SMART function ensuring balanced picture brightness level during IR illuminator operation
- Optional equipment: NV-RCB2 wire remote controller
- Power supply: 12 VDC

Functions available from NV-RCB2 remote controller:

- Electronic Day/Night function
- Wide Dynamic Range (WDR) for enhanced image quality in diverse light conditions
- Digital Noise Reduction (DNR)
- High Light Compensation (HLC)
- Privacy zones: 8
- Other functions: mirror picture effect, negative, image sharpness adjustment, motion detection
- User friendly OSD

Specificatii	Description
Pick-up Element	1/3" SONY Super HAD II color CCD imager
Number of effective pixels	752 (H) x 582 (V)
Horizontal Resolution	600 TVL
Min. Illumination	0.2 lx/F=2.0, 0lx (IR On)
S/N Ratio	More than 52 dB (AGC Off)
Electronic Shutter	Auto (AES): 1/50 s ~ 1/100 000 s
Auto Gain Control (AGC)	On
Auto Gain Control (AGC)	On (3 levels)/Off
Wide Dynamic Range (WDR)	On/Off
White Balance	4 modes: Manual/AWC/ATW 1 (2300~9500K)/ATW 2 (2000~11000K)
White Balance	ATW 1 (2300 ~ 9500 K)
Back Light Compensation (BLC)	On/Off
High Light Compensation (HLC)	On/Off
Synchronization	Internal
Day/Night Switching	Auto/Manual
Lens Type	Standard: f=3.6 mm
Angle of View (H)	67°

