

Color Vandal Proof Camera with Electronic Day/Night Function

NVC-BC4404V-black_archive



Caracteristici

- Electronic Day/Night function
- Horizontal resolution: 600 TVL
- Min. Illumination: 0.1 lx/F=1.2
- Wide Dynamic Range (WDR) for enhanced image quality in diverse light conditions
- Digital Noise Reduction (DNR)
- High Light Compensation (HLC)
- Auto iris DC lens: f=2.8 ~ 11 mm
- 3-axis camera module adjustment
- Privacy zones: 8
- Other functions: mirror picture effect, negative, image sharpness adjustment, motion detection
- Full configuration directly from the camera (user friendly OSD)
- IP 65
- Vandal proof housing
- Enclosure color: Black
- Power supply: 12 VDC

| Specificatii | Description |
|-------------------------------|-----------------------------------------------------------------------|
| Pick-up Element | 1/3" SONY Super HAD II CCD imager |
| Horizontal Resolution | 600 TVL - color mode, 650 TVL - b/w mode |
| Min. Illumination | 0.1 lx/F=1.2 - color mode (1/50 s), 0.01 lx/F=1.2 - b/w mode (1/50 s) |
| S/N Ratio | More than 52 dB (AGC Off) |
| Electronic Shutter | Auto (AES): 1/50 s ~ 1/100 000 s |
| Auto Gain Control (AGC) | On (3 levels)/Off |
| Wide Dynamic Range (WDR) | On/Off |
| White Balance | 4 modes: Manual/AWC/ATW 1 (2300~9500K)/ATW 2 (2000~11000K) |
| Back Light Compensation (BLC) | On/Off |
| High Light Compensation (HLC) | On/Off |
| Synchronization | Internal |
| Day/Night Switching | Auto/Manual |
| Filter Delay | 1 ~ 30 s |
| Lens Type | Auto iris DC: f=2.8 ~ 11 mm |
| Angle of View (H) | 81° ~ 24.6° |
| Flickerless function | On/Off |
| Video Output | 1.0 Vp-p/75 Ohm (BNC) |
| Set-up | On Screen Display (OSD) |

| Specificatii | Description |
|-----------------------|------------------------------------------------------------------------------------------------------------------------|
| Privacy Zones | 8 |
| Other Functions | Digital Noise Reduction (DNR), Motion detection, Various picture effects: Mirror, Negative, Image sharpness adjustment |
| Power Supply | 12 VDC |
| Power Consumption | 1.5 W |
| Operating Temperature | -10°C ~ 45°C |
| Relative Humidity | 30% ~ 80% (non-condensing) |
| Dimensions (mm) | 135 (Ø) x 97 (H) |
| Weight | 290 g |